

super forrest





1800 | 2100 | 2600

STOCKER-CREW

A trading division of ALVECO PTY. LTD. (ABN: 40 074 146 535)
 Postal Address: PO Box 203, Warners Bay, NSW 2282
 Telephone: (02) 4954 8900 Fax: (02) 4954 8902
alveco@ceinternet.com.au




USE: For mulching wild strong vegetation, scrub, bushes, plants, branches, etc

| MODEL | A cm | B cm | C cm | D cm | E cm |  |  |  |  |
|--------------------|---------|---------|---------|---------|---------|---|---|---|---|
| SUPER FORREST 1800 | 220 | 110 | 140 | 110 | 180 | 45 | 6+6 | 2900 | MAX 265 HP |
| SUPER FORREST 2100 | 254 | 110 | 140 | 110 | 211 | 45 | 6+6 | 3200 | MAX 265 HP |
| SUPER FORREST 2600 | 299 | 110 | 140 | 110 | 260 | 45 | 6+6 | 3600 | MAX 265 HP |

• **STANDARD EQUIPMENT**

- PTO 1000 RPM - 1" 3/4 Z 20 DIN 9611
- GEARBOX WITH FREE WHEEL
- BONNET WITH HYDR. CYLINDERS AND RAKES
- FIXED LEVELLING SKIDS
- ROTOR SHAFT Ø 630 MM
- LINKAGE CAT. III
- DOUBLE TRANSMISSION WITH BELTS AND AUTOMATIC BELTTENSOR
- FIXED TOOLS IN TUNGSTEN
- MAX. POWER TRANSMISSION: HP 265
- FRONT PROTECTION CHAINS
- HYDR. SELF POSITIONING OF THE GEAR BOX



FIXED TOOLS IN TUNGSTEN



AUTOMATIC BELTS TENSIONERS



OPTIONAL:

HYDR. SELF POSITIONING OF THE GEAR BOX



OPTIONAL:

HYDRAULIC TRANSMISSION



OPTIONAL:

HYDR. ADJUSTABLE BUMPER



OPTIONAL:
cm 25
DEPTH SKIDS